

MODEL TA-33-M

- 10, 15, 20 Meter
- 3 Element
- No measuring
- Pre-drilled
- Color coded
- 18-8 & 300 series Stainless Steel

Frequency, MHz	28, 21, 14	
Power Rating, watts CW	1500	
Power Rating, watts SSB	2500	
Power Rating, AM/FM	800	
Power Rating, RTTY/AMTOR	800	
VSWR at frequency	1.0/1 to 1.4/1	
Forward Gain, dBd 10 meters	8.3	
Forward Gain, dBd 15 meters	7.3	
Forward Gain, dBd 20 meters	6.5	
Front-to-Back Ratio, dB 10 meters	20	
Front-to-Back Ratio, dB 15 meters	20	
Front-to-Back Ratio, dB 20 meters	20	
Boom Length	14 ft	4.27 m
Maximum Element Length	28 ft	8.53 m
Turning Radius	15.5 ft	4.72 m
Mast Size hardware (equipped)	1.5 in	3.81 cm
Assembled weight	37 lbs	16.78 kg
Wind Surface Area	5.7 sq ft	.530 sq m
Wind Load, EIA Standard 80 MPH	114 lbs	51.71 kg
Warranty	2	
Recommended Coax	Hyperflex 500 / RG-213	



Mosley TA-33-M with TA-40-KR added.