

MODEL TA-34-XL

- 10, 15, 20 Meter
- 4 Element
- No measuring
- Pre-drilled
- Color coded
- 18-8 & 300 series Stainless Steel

Frequency, MHz	28, 21, 14	
Power Rating, watts CW	1500	
Power Rating, watts SSB	2500	
Power Rating, AM/FM	600	
Power Rating, RTTY/AMTOR	600	
VSWR at frequency	1.0/1 to 1.60/1	
Forward Gain, dBd 10 meters	9.5	
Forward Gain, dBd 15 meters	9.1	
Forward Gain, dBd 20 meters	8.2	
Front-to-Back Ratio, dB 10 meters	18	
Front-to-Back Ratio, dB 15 meters	18	
Front-to-Back Ratio, dB 20 meters	18	
Boom Length	21 ft	6.40 m
Maximum Element Length	28 ft	8.53 m
Turning Radius	17.75 ft	5.41 m
Mast Size hardware (equipped)	2 in	5.08 cm
Assembled weight	68 lbs	30.84 kg
Wind Surface Area	6.9 sq ft	0.841 sq m
Wind Load, EIA Standard 80 MPH	164 lbs	74.39 kg
Warranty	2	
Recommended Coax	Hyperflex 500 / RGG-213	



Mosley TA-34-XL