

# MODEL TA-63-N

- 6, 10, 12, 15, 17, 20 Meter
- 3 Active Elements on 6, 10, 12, 15, 17, 20
- Good all-around performance
- No measuring
- Pre-drilled
- Color coded

<b>Frequency, MHz</b>	50, 28, 24, 21, 18, 14	
<b>Power Rating, watts CW</b>	1500	
<b>Power Rating, watts SSB</b>	2500	
<b>Power Rating, AM/FM</b>	600 / 250 (6 meters)	
<b>Power Rating, RTTY/AMTOR</b>	600 / 250 (6 meters)	
<b>VSWR at frequency</b>	1.0/1 to 1.65/1	
<b>Forward Gain, dBd 6 meters</b>	6.9	
<b>Forward Gain, dBd 10 meters</b>	7.9	
<b>Forward Gain, dBd 12 meters</b>	7.1	
<b>Forward Gain, dBd 15 meters</b>	6.9	
<b>Forward Gain, dBd 17 meters</b>	6.7	
<b>Forward Gain, dBd 20 meters</b>	6.5	
<b>Front-to-Back Ratio, dB 6 meters</b>	20	
<b>Front-to-Back Ratio, dB 10 meters</b>	16	
<b>Front-to-Back Ratio, dB 12 meters</b>	8	
<b>Front-to-Back Ratio, dB 15 meters</b>	13	
<b>Front-to-Back Ratio, dB 17 meters</b>	12	
<b>Front-to-Back Ratio, dB 20 meters</b>	10	
<b>Boom Length</b>	14 ft	4.27 m
<b>Maximum Element Length</b>	29.5 ft	8.99 m
<b>Turning Radius</b>	16.3 ft	4.97 m
<b>Mast Size hardware (equipped)</b>	2 in	5.08 cm
<b>Assembled weight</b>	57 lbs	25.86 kg
<b>Wind Surface Area</b>	6.9 sq ft	.641 sq m
<b>Wind Load, EIA Standard 80 MPH</b>	160 lbs	72.58 kg
<b>Warranty</b>	2	
<b>Recommended Coax</b>	Hyperflex 500 / RG-213	

