

UBZ-LJ8 Kenwood Specs

Technical Specifications

Number of Channels	8
Talk Groups	38 (CTCSS)
Operating Temperature Range	-20 °C to + 55 °C
Power Supply	4.5 DC (3 AA Cells) or 3.6 DC V (optional UPB-1 NiCad Pack)
Dimensions	55.5 x 103.9 x 26 mm - Projections not included -
Weight (net)	180 g
Range = approx. 3 km under normal conditions	Yes

Receiver Specifications

Audio Output	90 mW (Loudness Off)
Reception	Double Super Heterodyne Reception

Transmitter Specifications

RF Power Output	0.5 W (PMR446 standard)
-----------------	-------------------------

PMR General Features

<u>10 Call Alert Tones</u>	Yes
<u>Auto Channel Select</u>	Yes
<u>Auto Power Off</u>	Yes
<u>Battery Saver Mode</u>	Yes
<u>Battery Status Indicator</u>	Yes
<u>Body Colour</u>	Black
<u>Character Display (Alphanumeric)</u>	Yes
<u>Compact Design</u>	Yes
<u>Ease of Operating Use</u>	Yes
<u>Internal VOX Ready</u>	Yes
<u>Key Beep On/Off</u>	Yes
<u>Key Lock</u>	Yes
<u>Long Battery Duration</u>	Yes
<u>Loudness Feature</u>	Yes
<u>Monitor Button</u>	Yes
<u>Number of Channels</u>	8 Channels
<u>QT (CTCSS)</u>	Yes
<u>Scan</u>	Yes
<u>"Talk Back" Scanning Function</u>	Yes
<u>Time-Out Timer</u>	Yes
<u>Voice Inversion Scrambler</u>	Yes

PMR Construction Features

Compatilby with other PMR446 brands Yes

Options

Choice of 3 AA Cells or optional UPB-1 NiCad Pack Yes

Accessory Features

Operating Voltage Range 3.4 DC ~ 5 V

Applicable Standards

Measurement - EN Standards Yes

www.hfelectronics.be